

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) An exercise device for leg exercises, the device comprising:
 - a pair of foot pedals;
 - a pair of actuating rods connected to the foot pedals;
 - a bearing block having an aperture, the rods telescoping through the aperture at a selectable actuation angle in response to pressure applied to the foot pedals;
 - a crossbar extending between arched base bars upon which the bearing block is secured; and
 - at least one resistive element attached between the rod and bearing block to provide resistance to pressure applied to the foot pedals.
2. (Currently Amended) The device of claim 1, wherein the selectable ~~incident~~ actuation angle is selected at an angle that causes a force centerline of the rods to be projected between endpoints of the arched base bars to limit tipping.
3. (Currently Amended) The device of claim 1, wherein a position of the crossbar along ~~the~~ an arch of the base bars is based on an interaction of crossbar position and actuation angle to provide a maximum incident angle of the base bars to ground.
4. (Original) The device of claim 1, wherein the resistive element is a rubber band.
5. (Original) The device of claim 1, wherein the resistive element is a spring.

6. (Original) The device of claim 1, wherein the resistive element is a pneumatic cylinder.

7. (Original) The device of claim 1, wherein the resistive element is a hydraulic cylinder.

8. (Original) The device of claim 1, further comprising an attachment bracket securing to a swivel bar of the foot pedals to connect the foot pedals to the actuating rods.

9. (Currently Amended) The device of claim 1, wherein the rods include a fastener for limiting ~~the~~ a stroke of the actuating rods.

10. (Original) The device of claim 1, wherein the foot pedals include a strap for securing the pedals to feet of an operator.

11. (Original) The device of claim 1, wherein the bearing block is attached to the crossbar by a fastener that is adjusted to space apart the bearing block and to select the actuation angle.

12. (Original) The device of claim 11, wherein the crossbar includes end fasteners for position the crossbar along the arched base bar so that an incident angle can be controlled to limit slippage.

13. (Original) The device of claim 12, further comprising grippers at each end of the base bars to limit slippage.

14. (Original) The device of claim 13, wherein the grippers are rubber.

15. (Original) The device of claim 1, wherein the base bars only contact ground at endpoints of the based bars.

16. (Currently Amended) An exercise device for operation only from a seated position, the device comprising:

a pair of base bars constructed like an arch and spaced apart from each other by a crossbar, only each ends of the base bars contact ground;

at least one bearing block secured to the crossbar by a fastening collar, the bearing block being locatable along the crossbar and rotatable around the crossbar for selecting a desired spacing and actuation angle of the bearing block; and

a banded resistive element connect to the bearing block ~~and a rod~~ for providing resistance to ~~the~~ a telescoping of ~~the~~ a rod into and out of ~~the~~ an aperture of the bearing block in response to a user depressing a foot pedal connected to the rod from a seated position.

17. (Currently Amended) The device of claim 16, wherein a position of the crossbar along ~~the arch of~~ the base bars is based on an interaction of crossbar position and actuation angle to provide a maximum incident angle of the base bars to ground to limit slippage and to insure a force centerline of the rods projects between endpoints of the base bars to limit tipping.

18. (Currently Amended) A device for exercising the legs while in a seated position comprising, in combination:

a frame for resting on the floor in front of a person in a seated position;

a pair of foot pedals;

a pair of actuating rods with one pedal mounted on the end of each rod such that each pedal is only mounted to the end of one of the actuating rods;

a bearing block carried by the frame and supporting each rod for reciprocating movement in a direction lengthwise of the rod when a person in a seated position pushes with their feet against said pedals; and

a resistive element connected between each rod and its bearing block to provide resistance to foot pressure applied to the pedals tending to shift the rod lengthwise against the resistance of the resistive element.

19. (Original) The device of claim 18, wherein the bearing block includes an aperture, the rods telescoping through the aperture at a selectable actuation angle in response to the foot pressure applied to the pedals.

20. (Currently Amended) The device of claim 19, wherein the actuation angle is selected so that a force centerline intersects ~~groung~~ ground between end points of the frame.

21. (Original) The device of claim 20, wherein the resistive element is a rubber band.

22. (Original) The device of claim 18, wherein the resistive element is a spring.

23. (Original) The device of claim 18, wherein the resistive element is a pneumatic cylinder.

24. (Original) The device of claim 18, wherein the resistive element is a hydraulic cylinder.